



Level 2 AC EV Residential Charger PWR-EVC11-48A/80A



Features:

- Stylish Durable Design
- Top Quality PC
- Anti-UV Treatment
- Automotive Coating
- IK08 & Type3 for Indoor & Outdoor Use
- Switchable Amperage
 - 48A, 70A, 80A
- RFID Card Reader
- LED Indicator
- LAN Standard, Wi-Fi
- Optional
- OCPP 1.6J
- SAEJ1772 Charging Plug with 18 ft Cable

PowerPortEVC.com





PWR-EVC11 Level 2 AC EV Residential Charger

Model No.	PWR-EVC11-48A/80A			
Input Voltage	208-240Vac			
Frequency	50-60Hz			
Amperage	48A	70A	80A	
Max. Power Output	11.5kW	16.8kW	19.2kW	
Approx. Miles Charged/Hour	80 miles charged/hour	100 miles charged/hour	125 miles charged/hour	
Function				
User Authentication	Optional RFID(ISO 14443)			
Network	LAN Standard (4G or Wi-Fi)			
Connectivity	Optional OCPP 1.6J			
Protection & Standard				
Certificate	ETL & FCC			
Charging Interface	SAE J1772 Compliant			
Safety Compliance	UL2594, UL2231-1/-2			
Multiple Protection	UVP, OVP, RCD (CCID20), SPD, Ground Fault Protection, OCP, OTP, Control Pilot Protection			
Environmental				
Operating Temperature	-22 Degrees F to 122 Degrees F			
Indoor/Outdoor	IK08, Type 3 Enclosure			
Relative Humidity	Up to 95% Non-Condensing			
Cable Length	18 ft Standard (25 ft Optional)			
Dimensions & Weights				
Product Dimensions	14.2" x 9.8" x 3.9"			
Package Dimensions	19.6" x 13.7" x 10.5"			
Net Weight	17.2 lbs.			
Gross Weight	19.6 lbs.			
EVC Unit Price				
PWR-EVC11-48A/80A				
Whole Sale Discounts	100 to 199 Units = 20.0%		200+ Units = 25.0%	
Pedestal Model No.	PWR-SP	PWR-BBP	PWR-BBPC	PWR-SSPC
Pedestal Description	Single Pedestal	Back-to-Back Single Pedestal	Back-to-Back Pedestal with Cable Management System	Dual Side-By-Side Pedestal with Cable Management System
Dimensions	10.6" x 6.1" x 54.9"	10.6" x 6.1" x 54.9"	15.7" x 8.7" x 78.2"	28.0" x 8.7" x 78.2"
Net Weight	28.7 lbs.	28.7 lbs.	97.0 lbs.	118.0 lbs.
Gross Weight	37.5 lbs.	37.5 lbs.	113.0 lbs.	140.0 lbs.
Product Material	Powder Coated Steel			
Pedestal Unit Price				